

SELECTION GUIDE

VARI LINEAR RETROFIT (VLR)

SUITABLE APPLICATIONS		
EDUCATION		✓
COMMERCIAL OFFICE		✓
RETAIL		✓
STORAGE FACILITY		✓
GROCERY STORE		✓
STAIRWELL		✓
INDUSTRIAL		✓
FEATURES & PERFORMANCE		
LUMEN RANGE		2,000 - 12,000
EFFICACY (lm/W) UP TO		180
CRI		>80
CCT OPTIONS		35, 40, 50
VOLTAGE		120-277V
DIMMING RANGE		100%-10% Standard (1% Dim Opt)
AMBIENT RANGE		-40°F - 123°F
SIZES		4FT & 8FT
WIDTH		Adjustable 2.8" to 5.5" (Custom Width Channel Options Available)
LENS STYLE		Flat or Curved
SENSOR MOUNTING		Integral & End
RATINGS		Damp, ETL
DLC		Standard & Premium
BAA COMPLIANT		✓
FIXTURE OPTION		✓
BASIC CONTROLS		
ON/OFF OCCUPANCY		✓
DAYLIGHT HARVESTING		✓
BI-LEVEL OCCUPANCY		✓
BI-LEVEL OCCUPANCY WITH PHOTOCELL		✓
ADVANCE GROUPING CONTROLS		
NUROAIR		✓
EASYSENSE		✓
LUTRON		✓