

# SELECTION GUIDE

## ROUND HIGH & LOW BAY SELECTION GUIDE



	ROUND HIGH BAY (RB5)	UFO LOW BAY (UFO-LB)	
SUITABLE APPLICATIONS	GYMNASIUM	✓	
	FITNESS CENTER	✓	
	WAREHOUSE	✓	
	DISTRIBUTION CENTER	✓	
	MANUFACTURING PLANT	✓	
	RACKING	✓	
	FOOD PROCESSING	✓	
	WET LOCATION	✓	✓
	COOLERS / FREEZER	✓	✓
	SAW MILL	✓	✓
FEATURES & PERFORMANCE	LUMEN RANGE	14,000 - 36,000	5,000 - 10,000
	EFFICACY (lm/W) UP TO	165	146
	CRI	>80	>80
	CCT OPTIONS	35, 40, 50 CCT SELECTABLE	30, 40, 50
	DISTRIBUTION	Wide	Wide & Narrow
	VOLTAGE	120-277V - Opt. 277-480V	120-277V - Opt. 347-480V
	SIZES	10" - 13"	16"
	HOUSING	Round	Round
	LENSING	Frosted & Clear Polycarbonate	Diffused Polycarbonate
	LIFE (L70)	>100K	>100K
	AMBIENT RANGE UP TO	-40°F - 122°F	-40°F - 145°F
	EMERGENCY	✓	✓
	RATINGS	WET, IP65, NSF, IK10	WET, IP66
	BAA COMPLIANT		✓
	DLC	Standard & Premium	Standard & Premium
	BASIC CONTROLS	ON/OFF OCCUPANCY	✓
ON/OFF OCCUPANCY W/ PHOTOCELL		✓	✓
ON/OFF OCCUPANCY W/ DAYLIGHT HARVESTING		✓	✓
DAYLIGHT HARVESTING		✓	✓
BI-LEVEL OCCUPANCY		✓	✓
BI-LEVEL OCCUPANCY W/ PHOTOCELL		✓	✓
ADVANCE GROUPING CONTROLS	NUROAIR	✓	✓
	SYNAPSE		✓