

VPAN *SELECT*

CONTROLS READY

LUMEN 
SELECTABLE

CCT 
SELECTABLE

BACK-LIT FLAT PANEL



Fixture Performance		Lumen Package	2700K		3000K		3500K		4000K		5000K		Watts ²
Model Numbers			Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy	Lumens	Efficacy	
VPAN14-25L/49L-U-CCTS-G2-CR		25L	2390.5	145.1	2541.7	152.4	2558.3	155.8	2615.0	156.1	2600.5	153.4	17.5
		28L	2666.9	144.4	2835.1	151.6	2853.3	153.5	2916.7	155.1	2899.7	152.7	19.4
		35L	3310.4	141.7	3519.8	150.2	3541.8	152.8	3621.3	153.7	3599.8	150.4	24.3
		42L	3999.9	139.0	4252.6	148.0	4279.5	151.3	4375.5	151.6	4350.1	147.5	29.0
		49L	4598.0	135.3	4888.3	145.8	4918.8	149.8	5029.5	150.1	5000.0	146.1	33.6
VPAN22-25L/49L-U-CCTS-G2-CR		25L	2420.2	145.2	2552.9	152.3	2568.2	154.2	2636.3	156.9	2626.0	157.5	16.7
		28L	2699.2	144.0	2846.8	151.3	2865.2	153.8	2939.9	156.4	2928.7	156.7	18.7
		35L	3350.3	140.9	3534.4	149.6	3556.7	152.6	3649.7	154.6	3635.2	153.4	23.6
		42L	4048.3	137.3	4270.3	147.0	4297.3	150.7	4410.3	152.2	4392.6	149.6	29.1
		49L	4653.0	135.0	4908.5	144.1	4939.6	148.3	5069.4	149.7	5049.1	145.1	34.0
VPAN24-28L/57L-U-CCTS-G2-CR		28L	2914.9	143.1	3035.3	152.2	3038.2	152.2	3179.9	157.3	3160.6	155.8	20.0
		35L	3519.8	141.3	3664.9	149.7	3669.6	151.5	3840.1	156.2	3816.8	154.1	24.5
		42L	4179.2	138.9	4351.9	148.1	4357.4	150.0	4559.7	154.6	4532.2	151.6	29.5
		49L	4784.2	136.6	4981.5	146.3	4987.8	148.4	5219.9	153.0	5187.4	149.0	35.0
		57L	5499.0	135.0	5726.0	142.6	5733.0	145.3	5940.0	149.6	5963.0	146.8	41.0
VPAN24-49L/77L-U-CCTS-G2-CR		49L	4638.6	140.4	4822.0	148.1	4856.3	150.8	4915.6	154.4	4921.0	151.7	32.4
		56L	5195.3	139.7	5392.1	147.4	5411.3	150.3	5568.0	153.8	5574.8	151.1	36.6
		63L	5861.9	138.9	6086.9	146.6	6141.3	149.7	6325.3	153.2	6325.0	150.5	42.4
		70L	6520.8	138.2	6778.9	145.9	6843.4	149.2	7046.7	152.6	7046.2	149.9	46.7
		77L	7248.0	137.4	7534.0	145.2	7588.0	148.6	7802.0	152.0	7811.0	149.3	51.9
¹ Values are nominal, see IES file for more detail ² Electrical data at 25C (77F). Actual wattage may differ by +/- 10% * Ambient Temperature range is -4°F - 104°F for all models													

VPAN *SELECT*

CONTROLS READY

BACK-LIT FLAT PANEL



VPAN Select
Controls Ready



VPAN Select
with Skylight Kit